

# BC2108PG2GF-250W

## Series

### 12-port Full Gigabit PoE Fiber Switch



#### Ideal for:



Telecom



Hotels & Resorts



Universities



Healthcare



Public Places



Airport



Transport



Industries

## OVERVIEW

The BC2108PG2GF-250W is a full gigabit unmanaged PoE fiber switch. It has 10\*10/100/1000M RJ45 ports and 2\*1000M SFP port slots. Port 1-8 can support IEEE802.3af/at PoE standard, single port PoE power up to 30W, Total power is 250W. As a PoE power supply device, it can automatically detect and recognize the power receiving equipment that meets the standard and supply power through the network cable.

It can automatically detect and identify the electrical equipment that meets the standard and supply power to it through the network cable, devices including wireless AP, IP camera, IP telephone and other PoE terminal equipment etc. In addition, it is suitable for networking system of hotel, campus, dormitory and small and medium enterprise etc. Unmanaged mode, plug and play, no configuration, easy to use.

## FEATURES

### 1. Full Gigabit access, gigabit TP/SFP port uplink

- All series supports "gigabit RJ45 port and Gigabit SFP port" combination, which enables users to flexibly build networking to meet the needs of various scenarios.
- Support non-blocking wire-speed forwarding.
- Support full-duplex based on IEEE802.3x and half-duplex based on backpressure.

### 2. Intelligent PoE power supply

- 8\*10/100/1000Base-T RJ45 ports, meeting the needs of security monitoring, teleconferencing system, wireless coverage, and other scenarios.
- IEEE802.3af/at PoE standard, without damaging non-PoE devices.
- Priority system for PoE port, it will supply power to the high priority level port first when the power budget is insufficient and avoid overwork of the device.

### 3. Stable and reliable

- Low power consumption, galvanized steel casing, the fan active cooling.
- Self-developed power supply, high redundancy design, providing a long term and stable PoE power output.
- Plug and play, no configuration, simple and convenient.
- CCC, CE, FCC, RoHS.
- The user-friendly panel, it can show the device status through the LED indicator of PWR, Link, L/A, PoE.

# BC2108PG2GF-250W

## Series

### 12-port Full Gigabit PoE Fiber Switch



## TECHNICAL SPECIFICATION

Model	BC2108PG2GF-250W
<b>Interface Characteristics</b>	
Fixed Port	8*10/100/1000Base-T PoE ports (Data /Power) 2*10/100/1000Base-T uplink RJ45 ports (Data) 2*1000Base-X uplink SFP ports (Data)
Ethernet Port	10/100/1000Base-T, auto-sensing, full/half duplex MDI/MDI-X
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or later UTP(≤100 meter) 1000BASE-T: Cat5e or later UTP(≤100 meter)
SFP Slot Port	Gigabit SFP optical fiber interface, default matching optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC)
Optical Cable	Multi-mode: 850nm /0 ~ 500M, single mode: 1310nm /0 ~ 40KM, 1550nm/ 0 ~ 120KM.
<b>Chip Parameter</b>	
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T IEEE802.3u 100Base-TX, IEEE802.3ab 1000Base-T IEEE802.3z 1000Base-X, IEEE802.3x
Forwarding Mode	Store and Forward(Full Wire Speed)
Switching Capacity	24Gbps (Non-blocking)
Forwarding Rate@64byte	17.86Mpps
MAC	4K
Buffer Memory	4M
Jumbo Frame	9.6K
LED Indicator	Power: PWR (green), network: Link, Link/Act (yellow), PoE: PoE(green) SFP port: L/A (green), speed : 1000M (green)
<b>Power</b>	
PoE Port	Port 1 to 8 IEEE802.3af/at @ POE
Power Supply Pin	Default 1/2 (+), 3/6 (-)
Max Power Per Port	30W; IEEE802.3af/at
Total PWR / Input Voltage	250W (AC100-240V)
Power Consumption	Standby:<10W, Full Load:<240W
Power Supply	Built-in power supply, AC100~240V 50-60Hz 4.1A
<b>Physical Parameter</b>	
Operation TEMP / Humidity	-20~+55°C;5%~90% RH Non condensing
Storage TEMP / Humidity	-40~+75°C;5%~95% RH Non condensing
Dimension (L*W*H)	270*181*44.5mm
Net /Gross Weight	<1.6kg /<2.2kg
Installation	Desktop, wall mounted, 19 inch 1U cabinet

# BC2108PG2GF-250W Series


## 12-port Full Gigabit PoE Fiber Switch



### Certification & Warranty

Lightning protection / Protection level	Lightning protection: 4KV 8/20us; Protection level: IP30
Certification	CCC;CE mark, commercial; CE/LVD EN60950;FCC Part 15 Class B; RoHS;
Warranty	3 years, lifelong maintenance.

### DIMENSION




- A.Working Indicator
- B.8\* 10/100/1000M PoE Ports
- C.2\*10/100/1000M Uplink Ports
- D.2\*10/100/1000M SFP Ports
- E.Power Input Port AC100-240V,50/60Hz

# BC2108PG2GF-250W Series

## 12-port Full Gigabit PoE Fiber Switch



### APPLICATION



### PACKING LIST

PACKING LIST	Content	Qty	Unit
	12-port full gigabit PoE fiber switch	1	SET
	AC Power Cable	1	SET
	Mounting Kits (Hanging Ear)	1	SET
	User Guide	1	PC



# 337 Forest Road,  
London, United Kingdom



+44 7859 571344



[info@bornelectronics.com](mailto:info@bornelectronics.com)



<https://bornelectronics.com/>