



24-Port 1/10G SFP L3 Managed Switch with 2 -40G SFP+ Extend



IPv6/IPv4
ACL/QoS

Redundant
Power



BC3224TM2QF

Key Features:

Ports: Provide 24*1/10G SFP with 2*40G SFP+ Slots

Wide Application: Designed for Wifi AP and IP Security camera.VoIP etc

Managed: Support remote web managed,VLAN and storm control and IPV6 management etc.
Layer3 Features, Static route, RIP, OSPF etc.

Surge protection: Protect the device from lighting surges and others electrical hazards

Safe and reliable: Provides defense against DOS, distributed denial of service, spoofing, and viruses

Easy to use and maintain: managed through Web, SNMP, Telnet, SSL and other methods

10G Series Layer 3 SFP Switch

BC3224TM2QF series switches are L3+ SFP+ Switches based on new generation of high-performance hardware and Benchu Operating System Platform (TOS). It provides a large capacity, high-density GE interfaces,and 40G uplink interfaces. With extensive service features and IPv6 forwarding capabilities, the BC3224TM2QF series switches is applicable to various scenarios. For example, it can be used as an access or aggregation switch on campus networks or an access switch in data centers. The S7500-24XF2TF series switches integrates many advanced technologies in terms of reliability, security, and energy saving. It employs simple and convenient means of installation and maintenance to reduce customers' OAM cost and help enterprise customers build a next-generation IT network.

Comprehensive QoS policies and security mechanisms

The BC3224TM2QF supports strict ARP learning, which prevents ARP spoofing attacks that exhaust ARP entries, The BC3224TM2QF also provides IP source guard to prevent DoS attacks caused by MAC address spoofing, IP address spoofing, and MAC/IP spoofing.

The BC3224TM2QF supports DHCP snooping, which generates user binding entries based on users' access interfaces, MAC addresses, IP addresses, IP address leases, and VLAN IDs. DHCP snooping discards invalid packets that do not match any binding entries, such as ARP spoofing packets and IP spoofing packets.This prevents hackers from using ARP packets to initiate man-in-the-middle attacks on campus networks.The interface connected to a DHCP server can be configured as a trusted interface to

Easy deployment and maintenance free

Supports SNMP v1/v2/v3 and provides flexible methods for managing devices. Users can manage the using the CLI and Web NMS. Supports SSH2.0 and other encryption, which makes management much more secured. Supports LLDP protocol for simpler management.

BC3224TM2QF

24 ports SFP 10G Managed Ethernet Switch with 4-40G SFP+

Technical Datasheet

Model	BC3224TM2QF	
Hardware Specifications		
Connector	24* 1G/10G Base-X SFP+ Slots	
Uplink port	2* 40G Base-X SFP+ Slots Extend	
Console	1 x RS232-to-RJ45 serial port (115200, 8, N, 1)	
LED Display	Power Indicator: PWR(green).	
	Network Indicator: Link(green)	
	SFP: Green	
Network Standard	IEEE802.3i 10 BASE-T	
	IEEE802.3u 100 BASE-TX	
	IEEE802.3ab/z 1000 BASE-TX	
	IEEE802.3ae 10G BASE-TX	
	IEEE802.3x Flow Control	
	IEEE802.3az EEE	
Switch Architecture	Store and Forward	
Transmission model	IEEE802.3X full-duplex and Backpressure half-duplex	
Switch Performance	Backplane bandwidth	760Gbps
	Packet forwarding rate	565.44Mpps
	MAC address	32768k
Power requirement	AC100-240V 50/60Hz	
ESD Protection	6KV ESD	
Dimension(W x D x H)	440 x 400 x 44.5mm(17.32in x 15.75in x 1.75in)	
Weight	<7kg	
Environment	Operating temperature: -20℃~55℃ , operating humidity: 5%~95%	
	Storage temperature: -40℃~75℃ , storage humidity: 5%~95%	
Safety	FCC Part15 Class A,CE,RoHs	

Layer 3 Functions		
Port Mirroring	TX / RX / both Many-to-1 monitor	
Vlan	802.1Q tagged-based VLAN Up to 256 VLAN groups, out of 4094 VLAN IDs 802.1ad Q-in-Q tunneling Voice VLAN;Protocol VLAN;Private VLAN (Protected port),GVRP	
Link Aggregation	IEEE 802.3ad LACP and static trunk Supports 8 groups of 8-port trunk	
Spanning Tree Protocol	STP, IEEE 802.1D Spanning Tree Protocol RSTP, IEEE 802.1w Rapid Spanning Tree Protocol MSTP, IEEE 802.1s Multiple Spanning Tree Protocol	
IGMP Snooping	IGMP (v2/v3) snooping IGMP querier Up to 256 multicast groups	

MLD Snooping	MLD (v1/v2) snooping, up to 256 multicast groups
Access Control List	IPv4/IPv6 IP-based ACL / MAC-based ACL
Reliability	ERPS(G.8032)
Layer 3 Functions	Static Routing for IPV4/IPV6 RIP V1/V2 ; RIPng rip for IPV6 OSPF v1/2 for ipv4 OSPFv3 for ipv6 BGP+ PIM: SM/SSM VRRP V1/2 for ipv4 VRRP V3 for ipv6
QoS	8 mapping ID to 8 level priority queues --- Port number --- 802.1p priority --- 802.1Q VLAN tag --- DSCP field in IP packet Traffic classification based, strict priority and WRR
Security	IEEE 802.1X port-based authentication Built-in RADIUS client to co-operate with RADIUS server RADIUS / TACACS+ user access authentication IP-MAC port binding MAC filtering Static MAC address DHCP Snooping and DHCP Option82 STP BPDU guard, BPDU filtering and BPDU forwarding DoS attack prevention ARP inspection IP source guard
Management Function	
Basic Management Interfaces	Web browser / Telnet / SNMP v1, v2c, V3 Firmware upgrade by HTTP / TFTP protocol through Ethernet network Remote / Local Syslog, System log, LLDP protocol, SNMP
Secure Management Interfaces	SSH, SSL, SNMP
SNMP MIBs	RFC 1213 MIB-II RFC 1215 Generic Traps RFC 1493 Bridge MIB RFC 2674 Bridge MIB Extensions RFC 2737 Entity MIB (Version 2) RFC 2819 RMON (1, 2, 3, 9) RFC 2863 Interface Group MIB RFC 3635 Ethernet-like MIB
Ordering Information	
BC3224TM2QF	24-Port 1/10G SFP L3 Managed Switch with 2 -40G SFP+ Extend , 6KV surge protection.(SFP not included)