




28 ports full Gigabit Managed Switch

BI824GM4F series

❖ Overview

BI824GM4F is a 28-port full Gigabit Managed Switch series that supports up to 24*10/100/1000M ports and 4*1000M SFP ports. It supports L2 management, such as QoS, VLAN, MSTP, Multi-broadcast, and ports management. It has a high anti-interference ability, the product supports 6KV surge protection, and 6KV contact / 8KV air ESD protection. It supports wall hanging and desktop installation, reliable and durable, and can be used in security network video monitoring, network engineering and other occasions.

❖ Picture



❖ Features

- With 24*10/100/1000M downlink ports, 4*1000M SFP ports;
- Supports L2 management, such as QoS, VLAN, MSTP, Multi-broadcast and ports management ;
- 6KV surge protection, 6KV contact / 8KV air ESD protection;
- Supports working temperature -30°C~60°C;
- Supports wall hanging and desktop installation.



28 ports full Gigabit Managed Switch

BI824GM4F series


❖ Specifications

Parameter	Specifications
Power supply	AC power supply
Range of voltage	AC100-240V, 50/60Hz
Consumption	Self-consumption<25W.
Downlink ports	Ports 1~24 10/100/1000Base-TX RJ45
Uplink ports	25~28 ports: 1000M SFP slots
Console port	RJ45 to serial port (38400, 8,N,1)
Reset key	Short press restart, >5s press recovery to default
Cable and distance	Use cat5e/6, 100m max
Standard	IEEE802.3, IEEE802.3u, IEEE802.3z
Switch fabric	56Gbps
Though put	41.66Mpps
Buffer	4M
MAC address table	16K
Indicator	Power: 1 *red; Uplink25~28: 1000M SFP slots Downlink 1~24: On RJ45 green LEDs indicate Link/Act
Protection	Surge: 6KV, standard: IEC61000-4-5 ESD: 6KV: contact / 8KV: air, standard:IEC61000-4-2
Working temperature	-30℃~65℃
Storage temperature	-40℃~85℃
Humidity	0~95%(No condensation)
Dimension(L×W×H)	420mm×285mm×44mm
Material	Metal
Color	Black
Net-weight	4kg




28 ports full Gigabit Managed Switch BI824GM4F series

❖ Panel diagram



⚠ **Attention 1:** This product must be well grounded against lightning, please use better than 20# cable to connect the grounding terminal and ground.


❖ Application





28 ports full Gigabit Managed Switch BI824GM4F series

❖ Dimensions



❖ Order information

Model	Description
BI824GM4F	With 24*10/100/1000M downlink ports, 4*1000M SFP ports; Support L2 management, such as QoS, VLAN, MSTP, Multi-broadcast and ports management ; 6KV surge protection, 6KV contact / 8KV air ESD protection.

BORN ELECTRONICS LIMITED

ADDRESS:

#94A
Goldsmith Avenue
London
United Kingdom
Phone: +4479 1989 8604
Email: info@bornelectronics.com

WARRANTY:

2 YEARS (EXPANDABLE UPTO 4 YEARS)

WEBSITE: <http://bornelectronics.com/>