

BC2224PG2F-400W

24Ports Gigabit PoE Switch



Key Features:

- Ports:** Provide 24*10/100/1000Mbps PoE ports and 2*1.25Gbps SFP Uplink
- PoE Standard:** IEEE802.3af/at Power over Ethernet (PoE) Compliant
- Total Power:** Total power budget of 400W and 30W for all single PoE ports
- Self-adaption:** RJ45 port supports 10/100/1000Mbps Auto MDI/MDIX
- Wide Application:** Designed for Wifi AP and IP Security camera.VoIP etc
- Surge protection:** Protect the device from lightning surges and others electrical hazards
- Considerate Design:** Rack mount installation with fanless design
- Easy to use:** Plug and play, No configuration required


Versatile PoE Port

Featuring 24* 10/100/1000Mbps PoE ports which support IEEE802.3af/at standard and 2 Gigabit SFP Uplink. the PoE switch provides Maximun power budget of 400W and 30W for single PoE ports sepectively,allowing users to have several different Networking products configured



Surge Protection Design

Reaching 6KV surge protection, the PoE ports owns the capacity to keep the PoE Switch from lightning strikes and other electrical surges, offering reliable performance even in some harsh environments.



Gigabit SFP Uplink Port

With SFP module slot available, the SFP uplink port is ideal for connecting the switch to the network's backbone, providing more than enough bandwidth and stability for ultra high speed data transferring, Beside the SFP can transmitte the date with Max 100Km distance with more economic solution

BC2224PG2F-400W

24Ports Gigabit PoE Switch



Technical Datasheet

Model	BC2224PG2F-300W	
Hardware Specifications		
Connector	24* 10/100/1000MBASE-T RJ45 auto MDI/MDIX ports 2* 1.25G Base-X SFP Slots	
PoE Port	24* 10/100/1000Mbps POE PSE port	
SFP	Single fiber/Dual fiber supported. Distance vary the module	
Thermal Fan	Fanless Design	
LED indicators	Power Indicator: PWR(green). Network Indicator: Link(yellow) PoE Working Indicator: PoE(green)	
Switch Architecture	Store and Forward	
Transmission model	IEEE802.3X full-duplex and Backpressure half-duplex	
Switch Performance	Backplane bandwidth	64Gbps
	Packet forwarding rate	42Mpps
	MAC address	8k
Power requirement	AC100-240V 50/60Hz	
ESD Protection	6KV ESD	
Dimension(WxDxH)	440mm x 260mm x 44.5mm(17.32in x 10.24in x 1.75in)	
Weight	<5kg	

Power over Ethernet (PoE) Specifications

Network standard	IEEE802.3i 10 BASE-T
	IEEE802.3u 100 BASE-TX
	IEEE 802.3ab Gigabit 1000BASE-T
	IEEE 802.3z Gigabit SX/LX
	IEEE802.3x Flow Control
	IEEE802.3af Power over Ethernet
	IEEE802.3at Power over Ethernet
	IEEE802.3az EEE


BC2224PG2F-400W

24Ports Gigabit PoE Switch



PoE Standard	IEEE 802.3af Power over Ethernet/PSE IEEE 802.3at Power over Ethernet Plus/PSE
PoE Supply Type	1/2(+), 3/6(-) End-span
PoE Power Output	Per Port 52V DC, 300mA. max. 15.4 watts (IEEE 802.3af) Per Port 52V DC, 600mA. max. 30 watts (IEEE 802.3at)
PoE Power budget	400W
Environment	
Safety	FCC Part15 Class A, CE, RoHs
Environment specification	Operating temperature: -20°C~55°C , operating humidity: 5%~95% Storage temperature: -20°C~75°C , storage humidity: 5%~95%

Interfaces




BC2224PG2F-400W


24Ports Gigabit PoE Switch



Structure Diagrams



Applications



Ordering Information

BC2224PG2F-400W

24 Ports 10/100/1000Mbps PoE switch with 2 Gigabit SFP Uplink, 6KV surge protection, IEEE802.3af/at



337 Forest Road,
London, United Kingdom



+44 7859 571344



info@bornelectronics.com



https://bornelectronics.com/