


## BIQ6202BPD1G

1\*10/100/1000BaseTX RJ45

2\*10/100/1000BaseTX RJ45 Ports

IP67 Gigabit PoE++ Extender



### Ideal for:



Telecom



Hotels & Resorts



Universities



Healthcare



Public Places



Airport



Transport



Industries

## OVERVIEW


BIQ6202BPD1G is a durable networking solution for outdoor and industrial use. It includes 1 x 10/100/1000BaseTX RJ45 port and 2 x 10/100/1000BaseTX RJ45 ports for high-speed connectivity and network expansion. With an IP67-rated waterproof and dustproof enclosure, it performs reliably in harsh conditions. PoE++ support provides up to 60W per port, delivering both power and data to devices like cameras and access points, making it perfect for demanding environments.

## BIQ6202BPD1G

1\*10/100/1000BaseTX RJ45

2\*10/100/1000BaseTX RJ45 Ports

IP67 Gigabit PoE++ Extender



## SPECIFICATIONS


Model No.	BIQ6202BPD1G
Fixed Port	1*10/100/1000Base-TX in 2*10/100/1000Base-TX out
PoE in	Supports IEEE802.3af/at/bt, max 120W PoE in Supports Passive DC37-57V in MAX 120W
PoE in Pin	12+ 45+ 36- 78-
PoE OUT	OUT1 Supports IEEE802.3af/at/bt, max 90W PoE out OUT2 Supports IEEE802.3af/at, max 30W PoE out
PoE OUT Pin	Bt: 12+ 45+ 36- 78- Af/at: 12+ 36-
PoE Dog	PoE auto execution detection and resets fault device, when PoE is on
Bandwidth	4Gbps
Packet Forwarding	2.88Mpps
MAC	2K
Buffer	2.5M
POE in Transmission Distance	10BASE-T: Cat3,4,5 UTP(≤250 meter) 100BASE-TX: Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(100 meter)
POE out Transmission Distance	10BASE-T: Cat3, 4, 5 UTP(≤250 meter) 100BASE-TX: Cat5 or later UTP(150 meter) 1000BASE-TX: Cat6 or later UTP(100 meter)
LED Indicator	PoE in: LED witch bt or af/at POE out: on LED Port: LAN link onLED LAN SPEED 1G LED PoEdog: on led(inbox)
Operating Temperature/Humidity	-40~+80° C; 5%~90% RH Non coagulation

## BIQ6202BPD1G

1\*10/100/1000BaseTX RJ45

2\*10/100/1000BaseTX RJ45 Ports

IP67 Gigabit PoE++ Extender




Storage Temperature/Humidity	-40~+90° C; 5%~95% RH Non coagulation
Dimension (W x D x H)	150*77*43mm 160*85*47mm
N.W/G.W (kg)	0.27kg/0.31kg
Lightning Protection level	6KV 8/20us
Installation	Desktop、 wall installation
Certificate	CE-EMC EN55032; CE-LVD EN62368; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)

## BIQ6202BPD1G

1\*10/100/1000BaseTX RJ45

2\*10/100/1000BaseTX RJ45 Ports

IP67 Gigabit PoE++ Extender



## ORDERING INFORMATION

PART NO.	Description
BIQ6202BPDG	1*10/100/1000BASE TX RJ45,2*10/100/1000BASE TX RJ4 Ports



# 337 Forest Road,  
London, United Kingdom



+44 7859 571344



[info@bornelectronics.com](mailto:info@bornelectronics.com)



<https://bornelectronics.com/>