


5 ports Industrial switch BI604E1F-MM-2KM series



❖ Overview

The BI604E1F-MM-2KM is a 5-port switch that supports up to 4*10/100M RJ45 ports and 1*100M SFP slot; It provides three modes of Extend, Default and VLAN to adapt to various complex environments.

BI604E1F-MM-2KM has a high anti-interference ability, the product supports 6KV surge protection, and 6KV contact / 8KV air ESD protection;

BI604E1F-MM-2KM supports Din-rail installation, reliable and durable, and can be used in security network video monitoring, network engineering and other occasions.

❖ Pictures



❖ Features

- ❖ With 4*10/100M RJ45 ports and 1*100M SFP slot;
- ❖ It provides three modes of Extend, Default and VLAN to adapt to various complex environments.
- ❖ Supports 6KV surge protection, 6KV contact / 8KV air ESD protection;
- ❖ Supports working temperature -40°C~75°C;
- ❖ Supports Din-rail installation, reliable and durable, and can be used in security network video monitoring, network engineering and other occasions.

5 ports Industrial switch BI604E1F-MM-2KM series




❖ Specifications

Parameter	Specifications
Power supply	Powered by power adaptor
Range of voltage	DC 12~60V
Consumption	Self consumption<5W
Downlink ports	Ports 1~4 10/100Base-TX RJ45ports
Uplink ports	Port 5 100Base-FX SFP slot
Cable and distance	Use cat5e/6,100m max.
Standard	IEEE802.3, IEEE802.3u
Switch fabric	1Gbps
Throughput	0.744Mpps
Buffer	1M
MAC address table	8K
Indicator	Power: 2 *red; Uplink 5: green LEDs indicate Link/Act Downlink 1~4: On RJ45 green LEDs indicate Link/Act
Protection	Surge: 6KV, standard: IEC61000-4-5 ESD: 6KV: contact / 8KV: air, standard:IEC61000-4-2
Working temperature	-40℃~75℃
Storage temperature	-40℃~85℃
Humidity	0~95%(No condensation)
Dimension(L×W×H)	101 mm×65 mm×36mm
Material	Aluminium
Colour	Black
Net-weight	350g


5 ports Industrial switch BI604E1F-MM-2KM series



❖ Panel diagram



● Back panel



⚠ Attention: This product must be well grounded against lightning, please use better than 20# cable to connect the grounding terminal and ground.

⚠ Attention: Extend, Default, VLAN mode: It can be selected by dip switch.

Extend: 1~4 ports Max. 250m transmission; 1~4 ports are isolated, only can communicate with the uplink ports; restrain the network storm; close flow control.


Default: Normal switch.

VLAN: 1~4 ports are isolated, only can communicate with the uplink ports; restrain the network storm; close flow control.


5 ports Industrial switch BI604E1F-MM-2KM series




❖ Application



❖ Dimensions



5 ports Industrial switch BI604E1F-MM-2KM series



❖ Order information

Model	Description
BI604E1F-MM-2KM	4*10/100M RJ45 ports, 1*100M SFP slot, double fiber, multi mode, 2KM, LC connector, without Power adaptor, DC 12V-60V power input. -40~75°C.



337 Forest Road
London, United Kingdom



Info@bornelectronics.com



+44 7859 571344



<https://bornelectronics.com>